

Brass Single Check Valves

To complement our fire sprinkler valve set, Applications Engineering Ltd offer a range of single WRAS approved brass check valves with sizes ranging from 1/2" BSP to 2" BSP. These can be purchased separately or fitted to our Valve

Part Numbers					
AE-SCV-15	15mm/G1/2" Female/Female				
AE-SCV-20	20mm/G3/4" Female/Female				
AE-SCV-25	25mm/G1" Female/Female				
AE-SCV-32	32mm/G1-1/4" Female/Female				
AE-SCV-40	40mm/G1-1/2" Female/Female				
AE-SCV-50	50mm/G2" Female/Female				




Material Specifications	
Body	DZR alloy
'O' ring	EPDM
Check Cartridges	Polypropylene





Technical Data				
Max. Temperature	90°C			
Max. Pressure	10 Bar			
End Connections	BS EN 10226			

Dimensions



Size	Α	В	С	D	kg
AE-SCV-15	1/2"	42	24	12.5	0.063
AE-SCV-20	3/4"	50	32	17	0.128
AE-SCV-25	1"	60	38	22	0.171
AE-SCV-32	1 1/4"	79	46	24	0.331
AE-SCV-40	1 ½"	84	53	30	0.532
AE-SCV-50	2"	101	64	38	0.850