

0)1825 764737 F: +44 (0)18

F: +44 (0)1825 768330 | E: info@appeng.co.uk

| W: appeng.co.uk

Brass Y Strainer

To complement our fire sprinkler valve set, Applications Engineering Ltd offer a range of Brass Y strainers with sizes ranging from $\frac{1}{2}$ " BSP to 4" BSP. These can be purchased separately or fitted to our Valve Sets

Part Numbers


AE-AGVB68050	15mm/G1/2" Female/Female
AE-AGVB68075	20mm/G3/4" Female/Female
AE-AGVB68100	25mm/G1" Female/Female
AE-AGVB68125	32mm/G1-1/4" Female/Female
AE-AGVB68150	40mm/G1-1/2"" Female/Female
AE-AGVB68200	50mm/G2" Female/Female
AE-AGVB68250	65mm/G2-1/2" Female/Female
AE-AGVB68300	80mm/G3" Female/Female
AE-AGVB68400	100mm/G4" Female/Female

Material Specifications	
Body	Brass
Bonnet	Brass
Strainer	Stainless Steel 304
Gasket	PTFE

Technical Data	
Working Temperature	0°C to 150°C
Max. Pressure	20 Bar



Dimensions



DN	L	н	E	D	d1	W	kg
1⁄2"	57	34.5	13	15	.6	0.9	.16
3⁄4"	72	39.5	15	18.5	.9	1.3	.28
1"	74.5	43	17	21	.9	1.3	.35
1 ¼"	95	54	18	29	.9	1.3	.62
1 ½"	105	61.5	18	38	.9	1.3	.83
2"	129	61.5	20	46	.9	1.3	1.2
2 ½"	142.5	93	20	58	.9	1.3	2
3"	160	93	22	64	.9	1.3	3
4"	245	143	30	100	.9	1.3	7